



## Plata Dorada Project

- Location:** 158 kilometers east of the city of Cuzco  
17 kilometers south west of the town of Marcapata  
2.5 hours' drive from Cuzco along paved highway
- Ownership:** 100% Camino Minerals Corporation
- Property:** 5 mineral concessions covering 1,800 hectares
- History:** Documents from the 18<sup>th</sup> century record mining activities by colonial miners at several locations within 50 kilometers of the project. There has been no organized mining on the project. Numerous pits and shallow underground workings are the result of recent artisanal mining activities.
- Geology:** The Plata Dorada Project is located in the Eastern Andes east southeast of the City of Cusco. The stratigraphic column is predominantly continental in origin with units from the Neoproterozoic and lower Paleozoic to Quaternary. The Paleozoic continental sediments are, in part, weakly metamorphosed and pierced by Permian to Tertiary granitic and andesitic intrusions. The Paleozoic strata have been folded, faulted and intruded as the result of subduction along the western margin of South America (INGEMMET, 1973).
- All of the concessions are underlain by Lower Paleozoic rocks of the Ordovician age Sandia Formation. The Sandia Fm. is a thick flysch with argillites, gray slates, sandstones, and shales. The rocks have been folded into a broad syncline with the beds dipping to the east or southeast. The strata have undergone low-grade regional metamorphism as evidenced by the slates and argillites.
- Structure:** The veins have been mapped, in the two zones, with strikes from 20° to 40° in the North zone and 335° to 355° in the South zone. The vein dips are reported as -65° to -82° in the North zone and -45° to -62° in South zone. These vein orientations appear to be sub-parallel to regional normal faulting related to the thrust fault found to the southwest of the property.
- Mineralization:** The mineralization is structurally hosted, polymetallic quartz-sulphide veins averaging 0.5 meters to 1.5 meters in width. Chip samples across the structures have metal values ranging from 0.3% to 8.7 % copper, 70 grams per tonne to +1,500 grams per tonne silver, and trace to 2.1 grams per tonne gold. Potential extensions of the known veins are buried under shallow cover.
- Deposit Type:** The copper-silver gold-bearing mineralization of the Plata Dorada Project area has been described as being a mesothermal, or orogenic quartz-sulphide vein deposit. Mesothermal quartz-sulphide veins are hosted by metamorphic country rocks such as the copper-gold-silver vein deposit of the Cozamin Mine, Zacatecas, Mexico, operated by Capstone Mining Corp.